

**CP STABILIZER
PRODUCT RANGE**



VOLTAGE STABILIZER

Technical Characteristic

- Input Voltage : 175/265V
- Output Voltage : 220V

Single-Phase Micro Processor Electronic

Code	Protection unit	Power (K.V.A.)	Characteristic of Product
S11 A1Y 01	S11 A1KY 01	2	Aluminium Wired
S11 A1Y 02	S11 A1KY 02	3.5	Aluminium Wired
S11 A1Y 03	S11 A1KY 03	5	Aluminium Wired
S11 A1Y 04	S11 A1KY 04	7.5	Aluminium Wired
S11 A1Y 05	S11 A1KY 05	10	Aluminium Wired
S11 A1Y 06	S11 A1KY 06	15	Aluminium Wired
S11 A1Y 07	S11 A1KY 07	20	Aluminium Wired
S11 A1Y 08	S11 A1KY 08	25	Aluminium Wired
S11 A1Y 09	S11 A1KY 09	30	Aluminium Wired
S11 A1Y 10	S11 A1KY 10	40	Aluminium Wired
S11 A1Y 11	S11 A1KY 11	50	Aluminium Wired



Technical Characteristic

- Input Voltage : 150/250V
- Output Voltage : 220V

Single-Phase Micro Processor Electronic

Code	Protection unit	Power (K.V.A.)	Characteristic of Product
S11 A1N 00	S11 A1KN 00	1	Aluminium Wired
S11 A1N 01	S11 A1KN 01	2	Aluminium Wired
S11 A1N 02	S11 A1KN 02	3.5	Aluminium Wired
S11 A1N 03	S11 A1KN 03	5	Aluminium Wired
S11 A1N 04	S11 A1KN 04	7.5	Aluminium Wired
S11 A1N 05	S11 A1KN 05	10	Aluminium Wired
S11 A1N 06	S11 A1KN 06	15	Aluminium Wired
S11 A1N 07	S11 A1KN 07	20	Aluminium Wired
S11 A1N 08	S11 A1KN 08	25	Aluminium Wired
S11 A1N 09	S11 A1KN 09	30	Aluminium Wired
S11 A1N 10	S11 A1KN 10	40	Aluminium Wired
S11 A1N 11	S11 A1KN 11	50	Aluminium Wired

Technical Characteristic

- Input Voltage : 300/460V
- Output Voltage : 380V

Three-Phase Micro Processor Electronic

Code	Protection unit	Power (K.V.A.)	Characteristic of Product
S11 A3Y 01	S11 A3KY 01	6	Aluminium Wired
S11 A3Y 02	S11 A3KY 02	10.5	Aluminium Wired
S11 A3Y 03	S11 A3KY 03	15	Aluminium Wired
S11 A3Y 04	S11 A3KY 04	22.5	Aluminium Wired
S11 A3Y 05	S11 A3KY 05	30	Aluminium Wired
S11 A3Y 06	S11 A3KY 06	45	Aluminium Wired
S11 A3Y 07	S11 A3KY 07	60	Aluminium Wired
S11 A3Y 08	S11 A3KY 08	75	Aluminium Wired
S11 A3Y 09	S11 A3KY 09	100	Aluminium Wired
S11 A3Y 10	S11 A3KY 10	120	Aluminium Wired
S11 A3Y 11	S11 A3KY 11	150	Aluminium Wired
S11 A3Y 12	S11 A3KY 12	200	Aluminium Wired
S11 A3Y 13	S11 A3KY 13	250	Aluminium Wired
S11 A3Y 14	S11 A3KY 14	300	Aluminium Wired
S11 A3Y 15	S11 A3KY 15	400	Aluminium Wired
S11 A3Y 16	S11 A3KY 16	500	Aluminium Wired
S11 A3Y 17	S11 A3KY 17	600	Aluminium Wired
S11 A3Y 18	S11 A3KY 18	800	Aluminium Wired
S11 A3Y 19	S11 A3KY 19	1000	Aluminium Wired
S11 A3Y 20	S11 A3KY 20	1250	Aluminium Wired
S11 A3Y 21	S11 A3KY 21	1600	Aluminium Wired
S11 A3Y 22	S11 A3KY 22	2000	Aluminium Wired
S11 A3Y 23	S11 A3KY 23	2500	Aluminium Wired
S11 A3Y 24	S11 A3KY 24	3250	Aluminium Wired



Technical Characteristic

- Input Voltage : 260/450V
- Output Voltage : 380V

Three-Phase Micro Processor Electronic

Code	Protection unit	Power (K.V.A.)	Characteristic of Product
S11 A3N 26	S11 A3KN 01	6	Aluminium Wired
S11 A3N 27	S11 A3KN 02	10.5	Aluminium Wired
S11 A3N 28	S11 A3KN 03	15	Aluminium Wired
S11 A3N 29	S11 A3KN 04	22.5	Aluminium Wired
S11 A3N 30	S11 A3KN 05	30	Aluminium Wired
S11 A3N 31	S11 A3KN 06	45	Aluminium Wired
S11 A3N 32	S11 A3KN 07	60	Aluminium Wired
S11 A3N 33	S11 A3KN 08	75	Aluminium Wired
S11 A3N 34	S11 A3KN 09	100	Aluminium Wired
S11 A3N 35	S11 A3KN 10	120	Aluminium Wired
S11 A3N 36	S11 A3KN 11	150	Aluminium Wired
S11 A3N 37	S11 A3KN 12	200	Aluminium Wired
S11 A3N 38	S11 A3KN 13	250	Aluminium Wired
S11 A3N 39	S11 A3KN 14	300	Aluminium Wired
S11 A3N 40	S11 A3KN 15	400	Aluminium Wired
S11 A3N 41	S11 A3KN 16	500	Aluminium Wired
S11 A3N 42	S11 A3KN 17	600	Aluminium Wired
S11 A3N 43	S11 A3KN 18	800	Aluminium Wired
S11 A3N 44	S11 A3KN 19	1000	Aluminium Wired
S11 A3N 45	S11 A3KN 20	1250	Aluminium Wired
S11 A3N 46	S11 A3KN 21	1600	Aluminium Wired
S11 A3N 47	S11 A3KN 22	2000	Aluminium Wired
S11 A3N 48	S11 A3KN 23	2500	Aluminium Wired
S11 A3N 49	S11 A3KN 24	3250	Aluminium Wired

VOLTAGE STABILIZER

Technical Characteristic

- Input Voltage : 175/265V
- Output Voltage : 220V

Single-Phase Micro Processor Electronic

Code	Protection unit	Power (K.VA.)	Characteristic of Product
S11 C1Y 00	S11 C1KY 00	1	Copper Wired
S11 C1Y 01	S11 C1KY 01	2	Copper Wired
S11 C1Y 02	S11 C1KY 02	3.5	Copper Wired
S11 C1Y 03	S11 C1KY 03	5	Copper Wired
S11 C1Y 04	S11 C1KY 04	7.5	Copper Wired
S11 C1Y 05	S11 C1KY 05	10	Copper Wired
S11 C1Y 06	S11 C1KY 06	15	Copper Wired
S11 C1Y 07	S11 C1KY 07	20	Copper Wired
S11 C1Y 08	S11 C1KY 08	25	Copper Wired
S11 C1Y 09	S11 C1KY 09	30	Copper Wired
S11 C1Y 10	S11 C1KY 10	40	Copper Wired
S11 C1Y 11	S11 C1KY 11	50	Copper Wired



Technical Characteristic

- Input Voltage : 150/250V
- Output Voltage : 220V

Single-Phase Micro Processor Electronic

Code	Protection unit	Power (K.VA.)	Characteristic of Product
S11 C1N 00	S11 C1KN 00	1	Copper Wired
S11 C1N 01	S11 C1KN 01	2	Copper Wired
S11 C1N 02	S11 C1KN 02	3.5	Copper Wired
S11 C1N 03	S11 C1KN 03	5	Copper Wired
S11 C1N 04	S11 C1KN 04	7.5	Copper Wired
S11 C1N 05	S11 C1KN 05	10	Copper Wired
S11 C1N 06	S11 C1KN 06	15	Copper Wired
S11 C1N 07	S11 C1KN 07	20	Copper Wired
S11 C1N 08	S11 C1KN 08	25	Copper Wired
S11 C1N 09	S11 C1KN 09	30	Copper Wired
S11 C1N 10	S11 C1KN 10	40	Copper Wired
S11 C1N 11	S11 C1KN 11	50	Copper Wired

Technical Characteristic

- Input Voltage : 300/460V
- Output Voltage : 380V

Three-Phase Micro Processor Electronic

Code	Protection unit	Power (K.VA.)	Characteristic of Product
S11 C3Y 01	S11 C3KY 01	6	Copper Wired
S11 C3Y 02	S11 C3KY 02	10.5	Copper Wired
S11 C3Y 03	S11 C3KY 03	15	Copper Wired
S11 C3Y 04	S11 C3KY 04	22.5	Copper Wired
S11 C3Y 05	S11 C3KY 05	30	Copper Wired
S11 C3Y 06	S11 C3KY 06	45	Copper Wired
S11 C3Y 07	S11 C3KY 07	60	Copper Wired
S11 C3Y 08	S11 C3KY 08	75	Copper Wired
S11 C3Y 09	S11 C3KY 09	100	Copper Wired
S11 C3Y 10	S11 C3KY 10	120	Copper Wired
S11 C3Y 11	S11 C3KY 11	150	Copper Wired
S11 C3Y 12	S11 C3KY 12	200	Copper Wired
S11 C3Y 13	S11 C3KY 13	250	Copper Wired
S11 C3Y 14	S11 C3KY 14	300	Copper Wired
S11 C3Y 15	S11 C3KY 15	400	Copper Wired
S11 C3Y 16	S11 C3KY 16	500	Copper Wired
S11 C3Y 17	S11 C3KY 17	600	Copper Wired
S11 C3Y 18	S11 C3KY 18	800	Copper Wired
S11 C3Y 19	S11 C3KY 19	1000	Copper Wired
S11 C3Y 20	S11 C3KY 20	1250	Copper Wired
S11 C3Y 21	S11 C3KY 21	1600	Copper Wired
S11 C3Y 22	S11 C3KY 22	2000	Copper Wired
S11 C3Y 23	S11 C3KY 23	2500	Copper Wired
S11 C3Y 24	S11 C3KY 24	3250	Copper Wired



Technical Characteristic

- Input Voltage : 260/450V
- Output Voltage : 380V

Three-Phase Micro Processor Electronic

Code	Protection unit	Power (K.VA.)	Characteristic of Product
S11 C3N 26	S11 C3KN 01	6	Copper Wired
S11 C3N 27	S11 C3KN 02	10.5	Copper Wired
S11 C3N 28	S11 C3KN 03	15	Copper Wired
S11 C3N 29	S11 C3KN 04	22.5	Copper Wired
S11 C3N 30	S11 C3KN 05	30	Copper Wired
S11 C3N 31	S11 C3KN 06	45	Copper Wired
S11 C3N 32	S11 C3KN 07	60	Copper Wired
S11 C3N 33	S11 C3KN 08	75	Copper Wired
S11 C3N 34	S11 C3KN 09	100	Copper Wired
S11 C3N 35	S11 C3KN 10	120	Copper Wired
S11 C3N 36	S11 C3KN 11	150	Copper Wired
S11 C3N 37	S11 C3KN 12	200	Copper Wired
S11 C3N 38	S11 C3KN 13	250	Copper Wired
S11 C3N 39	S11 C3KN 14	300	Copper Wired
S11 C3N 40	S11 C3KN 15	400	Copper Wired
S11 C3N 41	S11 C3KN 16	500	Copper Wired
S11 C3N 42	S11 C3KN 17	600	Copper Wired
S11 C3N 43	S11 C3KN 18	800	Copper Wired
S11 C3N 44	S11 C3KN 19	1000	Copper Wired
S11 C3N 45	S11 C3KN 20	1250	Copper Wired
S11 C3N 46	S11 C3KN 21	1600	Copper Wired
S11 C3N 47	S11 C3KN 22	2000	Copper Wired
S11 C3N 48	S11 C3KN 23	2500	Copper Wired
S11 C3N 49	S11 C3KN 24	3250	Copper Wired

POOL TRANSFORMER

Pool Transformer

Code	Characteristic of Product
S23 C00 00	220/12V 50VA Copper Wired - Polyester Body
S23 C00 01	220/12V 100VA Copper Wired - Polyester Body
S23 C00 02	220/12V 150VA Copper Wired - Polyester Body
S23 C00 03	220/12V 300VA Copper Wired - Polyester Body
S23 C00 04	220/12V 400VA Copper Wired - Polyester Body
S23 C00 05	220/12V 600VA Copper Wired - Polyester Body



Pool Transformer

Code	Characteristic of Product
S23 A00 00	220/12V 300VA Aluminium Wired - Polyester Body
S23 A00 01	220/12V 400VA Aluminium Wired - Polyester Body
S23 A00 02	220/12V 600VA Aluminium Wired - Polyester Body



VOLTAGE STABILIZER & TRANSFORMER



Stabilizer - With Metal Body

Code	Power (VA.)	Characteristic of Product
S14 1M0 00	500 VA	Voltage 130/290/220 Aluminium Wired
S14 1M0 01	1000 VA	Voltage 130/290/220 Aluminium Wired
S14 1M0 02	1500 VA	Voltage 130/290/220 Aluminium Wired
S14 1M0 03	1500K VA	Voltage 130/290/220 with condensator AL. Wired



Stabilizer - With Plastic Body

Code	Power (VA.)	Characteristic of Product
S14 1P0 00	500 VA	Voltage 130/290/220 Aluminium Wired
S14 1P0 01	1000 VA	Voltage 130/290/220 Aluminium Wired



Transformer - New Model 220/12 - 220/24

Code	Power (VA.)
S21 C12K 00	30 VA
S21 C12K 01	50 VA
S21 C12K 02	75 VA
S21 C12K 03	100 VA
S21 C12K 04	150 VA
S21 C12K 05	200 VA
S21 C12K 06	250 VA