

## TED Stabilizer WALL 500-1000VA

- Super slim wall mount design, compact size and space saving.
- Zero cross transfer technology integrated, longer operating life.
- High efficiency ultra slim toroidal transformer
- Full protections such as over voltage, under voltage, overload, over temperature, short circuit.
- Default delay 6 sec
- Digital display: input / output voltage, load rate, protection warnings, delay time
- CE / RoHS2.0 certified.



### Specifications

|                                  |                                                                            |             |
|----------------------------------|----------------------------------------------------------------------------|-------------|
| Model                            | TEDWALL500                                                                 | TEDWALL1000 |
| Power (W)                        | 300W                                                                       | 600W        |
| Input                            |                                                                            |             |
| Voltage range / Frequency Range  | 150V ÷ 270V AC / 45-65Hz                                                   |             |
| Input Connection                 | Schuko Power Cord                                                          |             |
| Output                           |                                                                            |             |
| Rated Output Voltage             | 230V AC                                                                    |             |
| Output Receptacle                | 2 x Schuko CEE 7/3                                                         |             |
| Precision                        | ±4%                                                                        |             |
| Frequency Range                  | 50Hz                                                                       |             |
| Response Time                    | < 1 second                                                                 |             |
| Waveform / Power factor          | Pure Sine Wave / 0.6                                                       |             |
| Efficiency                       | >96%                                                                       |             |
| General characteristics          |                                                                            |             |
| Protection                       | Over Voltage / Under Voltage / Overload / Overheat / Short-circuit / Surge |             |
| Ingress Protection / Noise Level | IP20 / <10dB at 1m distance with full load                                 |             |
| Operating Altitude               | <1000m                                                                     |             |
| Dimension D x W x H (mm)         | 175 x 300 x 72                                                             |             |
| Net Weight (kg)                  | 2,63                                                                       | 3,18        |
| Operating Humidity/Temperature   | 10% - 90%, non-condensing / -15°C ÷ 40°C                                   |             |

Due to continuous product improvements, program specifications are subject to change without notice